

Package: **lmimpute** (via **r-universe**)

June 24, 2026

Type Package

Title Missing Data Imputation via Language Models and Statistics

Version 0.1.0

Description Provides missing data imputation through two complementary engines: a large language model engine that communicates with the 'Anthropic' 'Claude' application programming interface for context-aware semantic imputation, and a fully self-contained offline engine implementing nineteen statistical and machine learning algorithms entirely in base R with no additional package dependencies. Offline methods include mean, median, mode, last observation carried forward, next observation carried backward, hot-deck, predictive mean matching, k-nearest neighbours, ordinary least-squares regression, Lasso with coordinate descent, Ridge with closed-form solution, Bayesian Ridge regression with evidence approximation following MacKay (1992), support vector regression with a radial basis function kernel, classification and regression trees, random forests, gradient boosting, iterative random forest imputation, principal component analysis imputation via iterative singular value decomposition, and nuclear-norm minimisation via singular value thresholding. When no API key is available the package automatically falls back to the offline engine, ensuring full operation in environments without internet access. Every imputed value is accompanied by a confidence score and a plain-language reasoning string, producing reproducible audit trails. The automatic method selector chooses the best algorithm per column based on data type, skewness, missingness rate, and inter-column correlations.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.3

Language en-US

Config/Needs/check spelling

Depends R (>= 4.1.0)

Imports httr2 (>= 1.0.0), methods, jsonlite (>= 1.8.0), cli (>= 3.6.0),

Suggests testthat (>= 3.0.0), knitr (>= 1.40), rmarkdown (>= 2.14), withr (>= 2.5.0)

Config/testthat/edition 3

VignetteBuilder knitr

BugReports <https://cran.r-project.org/submit.html>

NeedsCompilation no

Maintainer Sadikul Islam <sadikul.islamiasri@gmail.com>

Author Sadikul Islam [aut, cre] (ORCID: <<https://orcid.org/0000-0003-2924-7122>>), Rajesh Kaushal [aut]

Config/pak/sysreqs libssl-dev

Repository <https://sadikulislamiasri-hub.r-universe.dev>

Date/Publication 2026-06-23 15:28:33 UTC

RemoteUrl <https://github.com/cran/lmimpute>

RemoteRef HEAD

RemoteSha a4214af4b5757f2ff4d1c4d07aee9ebbce8db6e3

Contents

as.data.frame.lmi_result	3
lmi_diagnose	3
lmi_export	4
lmi_impute	5
lmi_impute_offline	8
lmi_methods	9
lmi_models	10
lmi_providers	10
lmi_set_api_key	11
lmi_set_model	12
print.lmi_result	13
summary.lmi_result	14

Index **15**

```
as.data.frame.lmi_result
```

Extract the imputed data frame from an lmi_result

Description

Convenience S3 method allowing `as.data.frame(result)` to extract the imputed data frame from an `lmi_result` object directly.

Usage

```
## S3 method for class 'lmi_result'  
as.data.frame(x, ...)
```

Arguments

`x` An object of class `lmi_result`.
`...` Currently unused. Included for S3 compatibility.

Value

The imputed data frame.

Examples

```
df <- data.frame(x = c(1, NA, 3))  
result <- lmi_impute_offline(df, verbose = FALSE)  
clean <- as.data.frame(result)
```

```
lmi_diagnose
```

Diagnose missing data in a data frame

Description

Analyses a data frame and prints a report on missing values, column types, and the number of unique observed values per column. No API calls are made. Use this function before `lmi_impute` to preview what will be imputed and to choose an appropriate method.

Usage

```
lmi_diagnose(data, na_strings = NULL)
```

Arguments

`data` A `data.frame` or `tibble`.

`na_strings` Character vector of additional strings to treat as NA (e.g. `c("N/A", "?", "-")`). Default `NULL`.

Value

Invisibly returns a `data.frame` with one row per column and columns `column`, `type`, `n_missing`, `pct_missing`, `n_unique`.

See Also

[lmi_impute](#), [lmi_impute_offline](#)

Examples

```
df <- data.frame(
  age = c(25L, NA, 35L, 40L),
  income = c(50000, 60000, NA, 80000),
  edu = c("BSc", NA, "MSc", "BSc"),
  stringsAsFactors = FALSE
)
lmi_diagnose(df)
lmi_diagnose(df, na_strings = "N/A")
```

`lmi_export`

Export imputed data and audit trail to files

Description

Writes the imputed data frame and the imputation audit trail to disk. Supports CSV (default) and RDS output formats. When `flag_suspicious = TRUE` was used in [lmi_impute](#), the suspicious-values table is also written.

Usage

```
lmi_export(
  result,
  path = tempdir(),
  prefix = "llmimpute",
  format = c("csv", "rds"),
  overwrite = FALSE
)
```

Arguments

result	An object of class <code>lmi_result</code> returned by <code>lmi_impute</code> or <code>lmi_impute_offline</code> .
path	Character string. Output directory. Created recursively if it does not exist. Default is the current working directory <code>"."</code> .
prefix	Character string prepended to output file names. Default <code>"llmimpute"</code> .
format	Character string. <code>"csv"</code> (default) or <code>"rds"</code> .
overwrite	Logical. Overwrite existing files? Default <code>FALSE</code> .

Value

Invisibly returns a named character vector of the file paths written.

See Also

[lmi_impute](#), [lmi_impute_offline](#)

Examples

```
df <- data.frame(
  age = c(25L, NA, 35L),
  income = c(50000, 60000, NA),
  stringsAsFactors = FALSE
)
result <- lmi_impute_offline(df, verbose = FALSE)
## Not run:
lmi_export(result, path = tempdir(), prefix = "my_study")

## End(Not run)
```

`lmi_impute`*Impute missing values using LLM or built-in statistical methods*

Description

Primary entry point for the **llmimpute** package. When an Anthropic API key is configured, missing values are filled using the Claude large language model, which reasons about each missing cell using the semantic meaning of column names, inter-column relationships, and domain knowledge. When no API key is available (or when `offline = TRUE`), the function transparently delegates to [lmi_impute_offline](#), which runs entirely in base R without internet access.

Usage

```

lmi_impute(
  data,
  domain = c("general", "healthcare", "financial", "hr", "survey", "scientific"),
  offline = FALSE,
  offline_fallback = TRUE,
  offline_method = c("auto", "mean", "median", "mode", "locf", "nocb", "hotdeck", "pmm",
    "knn", "linear", "lasso", "ridge", "bayesian_ridge", "svr", "decision_tree",
    "random_forest", "gradient_boost", "missforest", "pca_impute", "softimpute"),
  na_strings = NULL,
  cols = NULL,
  confidence = TRUE,
  reasoning = TRUE,
  flag_suspicious = FALSE,
  max_rows = 50L,
  knn_k = 5L,
  seed = 42L,
  verbose = TRUE
)

```

Arguments

<code>data</code>	A data frame or tibble containing the data to impute.
<code>domain</code>	Character string describing the data domain. Guides LLM reasoning. One of "general" (default), "healthcare", "financial", "hr", "survey", "scientific". Ignored in offline mode.
<code>offline</code>	Logical. If TRUE, always use the offline statistical engine regardless of API key availability. Default FALSE.
<code>offline_fallback</code>	Logical. If TRUE (default), switch to the offline engine when no API key is found instead of raising an error.
<code>offline_method</code>	Character. Offline imputation strategy passed to <code>lmi_impute_offline</code> . One of "auto" (default), "mean", "median", "mode", "locf", "nocb", "hotdeck", "pmm", "knn", "linear", "lasso", "ridge", "bayesian_ridge", "svr", "decision_tree", "random_forest", "gradient_boost", "missforest", "pca_impute", "softimpute".
<code>na_strings</code>	Character vector of additional strings to treat as NA, e.g. <code>c("N/A", "?", "-")</code> . Default NULL.
<code>cols</code>	Character vector of column names to impute. NULL imputes all columns with any missing values.
<code>confidence</code>	Logical. Include a confidence score (0-100) per imputed cell. Default TRUE.
<code>reasoning</code>	Logical. Include a one-sentence explanation per imputed cell. Default TRUE.
<code>flag_suspicious</code>	Logical. Ask the LLM to flag anomalous existing values (LLM mode only). Default FALSE.
<code>max_rows</code>	Integer. Maximum rows per API call chunk (LLM mode only). Default 50L.

knn_k	Integer. Neighbours for the "knn" offline method. Default 5L.
seed	Integer. Random seed for reproducible offline imputation. Default 42L.
verbose	Logical. Print progress messages. Default TRUE.

Value

An object of class `lmi_result`, a named list with:

data	The imputed data. frame.
imputations	data. frame audit trail: one row per imputed cell with columns row, col, original, imputed, confidence, reasoning.
suspicious	data. frame of flagged existing values (LLM mode, <code>flag_suspicious = TRUE</code> only). NULL otherwise.
summary	Named list of imputation statistics.
call	The matched call.

Engine selection

Situation	Behaviour
API key present, <code>offline = FALSE</code>	LLM imputation (Anthropic)
No key, <code>offline_fallback = TRUE</code>	Offline engine (silent)
No key, <code>offline_fallback = FALSE</code>	Error with guidance
<code>offline = TRUE</code>	Offline engine always

See Also

[lmi_impute_offline](#), [lmi_diagnose](#), [lmi_export](#), [print.lmi_result](#)

Examples

```
# Offline imputation (works with no API key)
df <- data.frame(
  age    = c(25L, NA, 35L, 40L, NA),
  income = c(50000, 60000, NA, 80000, 55000),
  edu    = c("BSc", NA, "MSc", "BSc", "PhD"),
  stringsAsFactors = FALSE
)

result <- lmi_impute(df)
result$data
result$imputations
summary(result)

# Force a specific offline method
result2 <- lmi_impute(df, offline = TRUE, offline_method = "random_forest")
```

```
## Not run:
# LLM mode requires a valid Anthropic API key
lmi_set_api_key() # reads ANTHROPIC_API_KEY from environment
result3 <- lmi_impute(df, domain = "hr")

## End(Not run)
```

`lmi_impute_offline` *Impute missing values using built-in statistical and ML methods (no API required)*

Description

Fully offline imputation using 20 methods from scratch in base R. No API key, no internet, no third-party packages needed.

Usage

```
lmi_impute_offline(
  data,
  method = c("auto", "mean", "median", "mode", "locf", "nocb", "hotdeck", "pmm", "knn",
    "linear", "lasso", "ridge", "bayesian_ridge", "svr", "decision_tree",
    "random_forest", "gradient_boost", "missforest", "pca_impute", "softimpute"),
  cols = NULL,
  na_strings = NULL,
  knn_k = 5L,
  n_trees = 50L,
  max_depth = 4L,
  shrinkage = 0.1,
  n_iter = 10L,
  lambda = 1,
  rank = 3L,
  seed = 42L,
  verbose = TRUE
)
```

Arguments

<code>data</code>	A data.frame or tibble.
<code>method</code>	One of: "auto", "mean", "median", "mode", "locf", "nocb", "hotdeck", "pmm", "knn", "linear", "lasso", "ridge", "bayesian_ridge", "svr", "decision_tree", "random_forest", "gradient_boost", "missforest", "pca_impute", "softimpute".
<code>cols</code>	Column names to impute. NULL = all missing columns.
<code>na_strings</code>	Extra strings treated as NA.
<code>knn_k</code>	Neighbours for knn. Default 5L.

n_trees	Trees for rf/gb/missforest. Default 50L.
max_depth	Tree depth. Default 4L.
shrinkage	Learning rate for gradient_boost. Default 0.1.
n_iter	Iterations for iterative methods. Default 10L.
lambda	Regularisation for ridge/lasso/bayesian_ride. Default 1.0.
rank	SVD rank for pca_impute/softimpute. Default 3L.
seed	Random seed. Default 42L.
verbose	Print progress. Default TRUE.

Value

An object of class `lmi_result`.

See Also

[lmi_impute](#), [lmi_methods](#)

Examples

```
df <- data.frame(
  age      = c(25, NA, 35, 40, NA),
  income   = c(50000, 60000, NA, 80000, 55000),
  edu      = c("BSc", NA, "MSc", "BSc", "PhD"),
  stringsAsFactors = FALSE
)
lmi_impute_offline(df)
lmi_impute_offline(df, method = "random_forest")
lmi_impute_offline(df, method = "softimpute")
```

`lmi_methods`

List all available offline imputation methods

Description

Prints all 20 methods grouped by category with usage guidance.

Usage

```
lmi_methods()
```

Value

Invisibly returns a `data.frame` of method metadata.

Examples

```
lmi_methods()
```

lmi_models	<i>List recommended models for each supported LLM provider</i>
------------	--

Description

Prints recommended model identifiers for every provider supported by [lmi_impute](#), including free-tier options. Use [lmi_set_model](#) to activate a model after choosing a provider with [lmi_set_api_key](#).

Usage

```
lmi_models()
```

Value

Invisibly returns a character vector of all model identifiers across every provider.

See Also

[lmi_set_model](#), [lmi_providers](#), [lmi_impute](#)

Examples

```
lmi_models()
```

lmi_providers	<i>List all supported LLM providers</i>
---------------	---

Description

Prints every LLM provider supported by [lmi_impute](#), grouped into cloud APIs, local servers, and custom endpoints, with free-tier indicators and required environment variables.

Usage

```
lmi_providers()
```

Value

Invisibly returns a character vector of provider names.

See Also

[lmi_set_api_key](#), [lmi_models](#)

Examples

```
lmi_providers()
```

lmi_set_api_key	<i>Configure the API key and LLM provider for llimpute</i>
-----------------	--

Description

Sets the API key and LLM provider used by LLM-mode imputation. Supports cloud APIs (Anthropic 'Claude', OpenAI, Google Gemini, Groq, Mistral, Cohere, OpenRouter, Together AI, Fireworks AI, DeepSeek, Perplexity, xAI Grok, AI21 Labs, Cerebras) and local servers (Ollama, LM Studio, Jan, llama.cpp, KoboldCpp, Text Generation WebUI). Any other OpenAI-compatible endpoint can be used via provider = "custom" with a base_url.

If no API key is configured, [lmi_impute](#) automatically falls back to the offline statistical engine. The package is fully functional without any API key.

Usage

```
lmi_set_api_key(
  api_key = NULL,
  provider = "anthropic",
  base_url = NULL,
  .session = TRUE
)
```

Arguments

api_key	Character string. Your API key. Not required for local providers (Ollama, LM Studio, Jan, llama.cpp, KoboldCpp, Text Generation WebUI). If NULL, the function reads from the provider's environment variable.
provider	Character string. Provider name. One of: "anthropic", "openai", "gemini", "groq", "mistral", "cohere", "openrouter", "together", "fireworks", "deepseek", "perplexity", "xai", "ai21", "cerebras", "ollama", "lmstudio", "jan", "llamacpp", "koboldcpp", "textgenwebui", or "custom". Default "anthropic".
base_url	Character string. Required only for "custom". For local providers you can override the default port here too, e.g. base_url = "http://localhost:9000/v1/chat/completions".
.session	Logical. Store for the current session only (default TRUE).

Value

Invisibly returns the API key string (or "" for keyless local providers).

See Also

[lmi_providers](#), [lmi_set_model](#), [lmi_impute](#)

Examples

```

## Not run:
## Cloud APIs
lmi_set_api_key("sk-ant-...", provider = "anthropic")
lmi_set_api_key("sk-...", provider = "openai")
lmi_set_api_key("AIza...", provider = "gemini") # free tier
lmi_set_api_key("gsk...", provider = "groq") # free tier
lmi_set_api_key("sk-or-...", provider = "openrouter") # free models
lmi_set_api_key("...", provider = "deepseek")
lmi_set_api_key("...", provider = "cerebras") # free tier

## Local servers (no key needed)
lmi_set_api_key(provider = "ollama")
lmi_set_api_key(provider = "lmstudio")
lmi_set_api_key(provider = "jan")
lmi_set_api_key(provider = "llamacpp")
lmi_set_api_key(provider = "koboldcpp")
lmi_set_api_key(provider = "textgenwebui")

## Any OpenAI-compatible endpoint
lmi_set_api_key("mykey", provider = "custom",
               base_url = "http://my-server:8000/v1/chat/completions")

## Override local port
lmi_set_api_key(provider = "ollama",
               base_url = "http://localhost:11435/api/chat")

## End(Not run)

```

lmi_set_model	<i>Set the LLM model used for imputation</i>
---------------	--

Description

Sets or retrieves the model identifier used by `lmi_impute` in LLM mode. The default model is determined by the active provider. Use `lmi_models` to see recommended models per provider.

Usage

```

lmi_set_model(model = NULL)

lmi_get_model()

```

Arguments

model	Character string. A valid model identifier for the active provider. If NULL, returns the current model without changing it.
-------	---

Value

Invisibly returns the active model string.

See Also

[lmi_set_api_key](#), [lmi_models](#)

Examples

```
lmi_get_model()

## Not run:
lmi_set_model("gpt-4o-mini")
lmi_set_model("gemini-1.5-flash")
lmi_set_model("llama-3.3-70b-versatile")
lmi_set_model("deepseek-chat")
lmi_set_model("llama3.2")          # Ollama local

## End(Not run)
```

```
print.lmi_result      Print an lmi_result object
```

Description

Displays a formatted summary of an imputation result in the console, including overall statistics, per-column imputation counts, and the first n imputed values with their confidence scores and reasoning.

Usage

```
## S3 method for class 'lmi_result'
print(x, n = 10L, ...)
```

Arguments

x An object of class `lmi_result` returned by [lmi_impute](#) or [lmi_impute_offline](#).

n Integer. Number of individual imputation rows to display. Default 10L.

... Currently unused. Included for S3 compatibility.

Value

Invisibly returns x.

Examples

```
df <- data.frame(
  age = c(25L, NA, 35L),
  income = c(50000, 60000, NA),
  stringsAsFactors = FALSE
)
result <- lmi_impute_offline(df, verbose = FALSE)
print(result)
```

summary.lmi_result	<i>Summarise an lmi_result object</i>
--------------------	---------------------------------------

Description

Returns a data.frame summarising imputation counts and confidence statistics per column, suitable for further analysis or reporting.

Usage

```
## S3 method for class 'lmi_result'
summary(object, ...)
```

Arguments

object	An object of class lmi_result.
...	Currently unused. Included for S3 compatibility.

Value

A data.frame with columns column, n_imputed, mean_confidence, min_confidence, max_confidence. Returns NULL invisibly when no imputations were performed.

Examples

```
df <- data.frame(
  age = c(25L, NA, 35L, 40L),
  income = c(50000, 60000, NA, 80000),
  stringsAsFactors = FALSE
)
result <- lmi_impute_offline(df, verbose = FALSE)
summary(result)
```

Index

`as.data.frame.lmi_result`, 3

`lmi_diagnose`, 3, 7

`lmi_export`, 4, 7

`lmi_get_model (lmi_set_model)`, 12

`lmi_impute`, 3, 4, 5, 5, 9–13

`lmi_impute_offline`, 4–7, 8, 13

`lmi_methods`, 9, 9

`lmi_models`, 10, 10, 12, 13

`lmi_providers`, 10, 10, 11

`lmi_set_api_key`, 10, 11, 13

`lmi_set_model`, 10, 11, 12

`print.lmi_result`, 7, 13

`summary.lmi_result`, 14